



Pro-Flex™ Outdoor Convenience Outlet

PFBBQ-2016

ITEM # SUBMITTED: _____

JOB NAME: _____

LOCATION: _____

ENGINEER: _____

CONTRACTOR: _____

PO #: _____

TAG: _____

APPLICATION

The Pro-Flex Grill Convenience Outlet Kit provides an outdoor rated Quick Disconnect Valve and 10' Quick Connect Gas Connector. This allows Pro-Flex CSST to be ran to a permanently mounted outlet box suitable for use with a Natural or LP Gas Grill. Natural Gas conversion kit not included.

INSTALLATION

Product installation and system testing shall be completed by a qualified installer in accordance with NFPA 54/ANSI Z223.1 (National Fuel Gas Code), state/local codes and the Pro-Flex Installation/Training Guide.

MATERIALS

- Quick Disconnect: brass
- Outlet Box: 304 Stainless Steel
- Flex connector: Elastomer coated, lined, strip wound steel

SPECIFICATIONS

- APPROVED GASES: **Natural Gas and LP [Propane] Gas**
- MAXIMUM FLOW CAPACITY: 60,000 btu/h @ 1/2 psi with 1" pressure drop
- MAX WORKING PRESSURE: 5 PSIG
- MAX TESTING PRESSURE: 40 PSI *
- TEMPERATURE RATING: -40° F/ -40° C—200° F/ 93.3° C
- INLET: 1/2" FIP
- OUTLET: 3/8" FEMALE FLARE SWIVEL
- LENGTH: 10'



Listed with CSA by manufacturer

Rev. 3.23

Pro-Flex™
Traditional CSST

FlakJacket™
Arc-Resistant CSST

HearthMaster™
Fireplace & Log Lighter
Valves, Bars, etc.

Pro-Poly™
Underground Gas
Piping System

