

Pro-Flex™ Pro-Poly Tee Fittings



PETE2- Series

ITEM # SUBMITTED: _____
JOB NAME: _____
LOCATION: _____
ENGINEER: _____
CONTRACTOR: _____
PO #: _____
TAG: _____

APPLICATION

The Pro-Poly™ Poly Tee Fitting is used join together 3 MDPE Gas pipes of the same diameter and SDR.

INSTALLATION

Product installation and system testing shall be completed by a qualified installer in accordance with NFPA 54/ANSI Z223.1 (National Fuel Gas Code), state/local codes and the Pro-Poly Installation/Training Guide.

MATERIALS

Nut and Main Body: Polypropylene

O-Ring: Nitrile

Spacer: Nylon

Grip Ring: Acetal

Stiffener: Acetal

SPECIFICATIONS

APPROVED GASES: **LP (PROPANE) & NATURAL GAS**

MAX OPERATING PRESSURE: **125 PSIG**

OPERATING TEMPERATURE RANGE: **-20° F— 180° F**

CODES, STANDARDS & LISTINGS:

Codes: NFPA 54, ICC Codes, UPC, UMC

Standards: ASTM F1924-2012

Listings: IAPMO File # 12082

ITEM NUMBERS:

PETE2-34C = 3/4" IPS SDR 11 Tee

PETE2-01C = 1" IPS SDR 11 Tee

PETE2-0114C = 1-1/4" IPS SDR 11 Tee

PETE2-02C = 2" IPS SDR11 Tee



Rev. 3.23

Pro-Flex™
Traditional CSST

FlakJacket™
Arc-Resistant CSST

HearthMaster™
Fireplace & Log Lighter
Valves, Bars, etc.

Pro-Poly™
Underground Gas
Piping System



Pro-Flex, LLC • P: 877.798.6291 • F: 765-798-6139 • E: sales@proflexcsst.com