

# Pro-Flex™ Bonding Clamps



## PFBC - Series

ITEM # SUBMITTED: \_\_\_\_\_  
JOB NAME: \_\_\_\_\_  
LOCATION: \_\_\_\_\_  
ENGINEER: \_\_\_\_\_  
CONTRACTOR: \_\_\_\_\_  
PO #: \_\_\_\_\_  
TAG: \_\_\_\_\_

### APPLICATION

The Pro-Flex™ Bonding Clamps are used is to be attached to EITHER a CSST Fitting OR a rigid pipe or rigid component at any point in the gas piping system downstream of the gas meter or second stage regulator in an accessible location.

### INSTALLATION

Product installation and system testing shall be completed by a qualified installer in accordance with NFPA 54/ANSI Z223.1 (National Fuel Gas Code), state/local codes and the Pro-Flex Installation/Training Guide.

### MATERIALS

Bolts: Stainless steel

Clamp: Bronze

#### Part Numbers :

PFBC-AB : 3/8" - 1/2" — 6/box

PFBC-CDE : 3/4" - 1 1/4" — 6/box

### SPECIFICATIONS

APROVED GASES: **Natural Gas and LP [Propane] Gas**

TEMPERATURE RATING: -20° F/ -28.9° C—200° F/ 93.3° C

### CODES, STANDARDS & LISTINGS:

**Codes:** NFPA 54, ICC Codes [IFGC, IRC, IPC, IMC], UPC, CAN/CSA B149.1, NFPA-70

**Standards:** ANSI LC1• CSA 6.26

**Listings:** Clamp is listed by its manufacturer to UL 467 Cat KDER



Rev 3.23

Pro-Flex™  
Traditional CSST

FlakJacket™  
Arc-Resistant CSST

HearthMaster™  
Fireplace & Log Lighter  
Valves, Bars, etc.

Pro-Poly™  
Underground Gas  
Piping System



Pro-Flex, LLC • P: 877.798.6291 • F: 765-798-6139 • E: sales@proflexcsst.com